

MULTI-ROOM AUDIO CONTROL

SpeakerCraft Control System Rediscover the First Choice in Sound.

The NEW SpeakerCraft MRA-664 is the whole home audio controller that delivers up to half a dozen unique music sources for amazing sound in every room of the house. This MRA is the first to integrate multi-room audio along with home theater control in a way that is simple to set up and brilliant to listen to.

SpeakerCraft's long-standing reputation for being bold and best in the audio space has been validated yet again with the introduction of this integrator-friendly controller. Using just a tablet or PC, an installer can quickly configure the MRA for sources, zone preferences, user interface customization and home theater control.

A job that might have once required hours of programming has been distilled down to a simple execution. And, for larger homes, two MRAs can be paired to create a six-source, 12-zone system. That means 12 rooms with music porting into each of them. Additionally, all zones are equipped with fixed or variable pre-outs, making it simple to add power

MRA-664

NEW

and volume with one of our NEW SpeakerCraft Amplifiers (SC2-50, SC2-100, SC2-150, SC12-30, or SC16-50).

38 years of continuous commitment to innovation and product excellence has been instrumental in shaping the intuitive user interface that renders identically across devices and can be managed from the NEW SpeakerCraft programmable sHR200 handheld remote, NEW SpeakerCraft sKP7 7-button keypad or NEW SpeakerCraft sTP7 7" touch panel, as well as an iPhone®, iPad® and Android® phones & tablets, and Windows® or Mac® computers. www.SpeakerCraft.com

Homeowners love SpeakerCraft because it delivers an unrivaled audio experience. Installers choose SpeakerCraft for its reliable performance. Simply put, this controller makes it possible to listen to any source, in any room, at any time. Rediscover the first choice in audio custom installations.

FEATURES:

- Six source, six zone audio controller - 4 zones amplified (Stackable to 2)
- Configuration software for ease of installation
- Control via handheld devices as well as SpeakerCraft keypad and touch panel controls
- Control of streaming content (Autonomic, Yamaha, AVRs,

Fusion Research, Vortex, S1 Digital, Sonos Connect)

- Control of legacy content devices: CD players, set top boxes, etc. via IR
- Control I/O (in/out) extender
- Meta Data Displays: The LCD display on the SpeakerCraft touch panel provides the valuable song, track, and artist information.
- Control of a media system via Pano IR. Extensive pre-defined IR database.
- Custom Tailored Sound: Independent bass, treble, and loudness controls enable the customization of each zone to optimize performance.
- Expandable to 12 Zones: Simply add another MRA-664 Controller to create a system with twelve zones.

FEATURES: (cont'd)

- Pre-Out Connections: If you need more power, each zone features pre-out connections to support the connection of higher powered amplifiers.
- 3rd Party control system compatible via API.
- Wide Selection of User Interfaces: Compatible with SpeakerCraft handheld and

wall mounted user interfaces as well as Windows, Mac and mobile devices.

- Extensive IR Code Library: Built into the controller and updated through the cloud.
- High-Performance, 8-Channel Digital Amplifier: The advanced digital amplifiers deliver 30 watts per channel to each zone (240 Watts Total System

Power – All Channels Driven). Low impedance capability (2.6Ω stable) provides speaker connection flexibility.

- System Configuration: Via tablet, Windows or Mac for quick and intuitive system set up.
- Six Source, Six Zone Multi-Room Controller: The MRA-664 independently distributes up to six audio sources to up to six zones.

SPECIFICATIONS:

Dimensions	17 1/4"W x 4 15/16"H x 12 7/8"D with feet (437 x 100 x 328 mm)
	Rackmount dimensions: 17 1/4"W x 3 1/2"H (2U) x 12 7/8"D without feet (437 x 88 x 328 mm)
Weight	18 lbs. (8,6 kg)
Power Supply	100-120 / 220-240 V~, 50 / 60 Hz
Fuse Rating	T5 AL, 250 V~
Power Consumption	200 W
Amplifier Power Output	30 watts/ch @ 8Ω
	45 watts/ch @ $4\Omega v$
THD	<0.10%, 1 watt output into 8Ω
Signal to Noise Ratio	>100db, 20Hz-20kHz unweighted
Audio Source Inputs	6 – analog, RCA connectors
Audio Zone Outputs	6 – 4 Amp + Preamp, 2 Preamp Only
Speaker Connections	(4) detachable + (4) pole terminals
IR Outputs	6 routable
Ethernet	1 RJ-45 10/100 BaseT
USB	1 Туре-А









Get your App: www.SpeakerCraft.com/MRASupport